

**TITLE 8:**  
**CONSTRUCTION SAFETY ORDERS**  
**CHAPTER 4, SUBCHAPTER 4, ARTICLE 28, SECTION 1698(e)1 and (2)**

**MORTAR, PLASTER OR FIREPROOFING MIXER GRID GUARDS**

Heard at the July 19, 2001, Public Hearing  
Adopted on September 20, 2001  
Filed with Secretary of State on October 23, 2001  
Effective November 22, 2001

**STANDARDS PRESENTATION  
TO  
CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD**

Attachment No. 1

Page 1 of 1

PROPOSED STATE STANDARD,  
TITLE 8, CHAPTER 4

Amend Section 1698(e) as follows:

§1698. Concrete and Masonry Equipment.

\*\*\*\*\*

(e) Mortar, Plaster or Fireproofing Mixers.

(1) ~~One year after the effective date of this regulation, g~~Grid guards on mortar, plaster or fireproofing mixers of 1 yard capacity or smaller shall have a grid opening not to exceed ~~4 inches square~~ 16 square inches with a minimum clearance of 5 inches from the top of the grid guard to the top of the mixing paddles.

(2) All mortar, plaster or fireproofing mixers of 1 yard capacity or smaller ordered or purchased after the effective date of this regulation shall be equipped with grid guards with an opening not to exceed ~~4 inches square~~ 16 square inches with a minimum clearance of 5 inches from the top of the grid guard to the top of the mixing paddles.

\*\*\*\*\*

Note: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.